

2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610 2611 2612 2613 2614 2615 2616 2617 2618 2619 2620 2621 2622 2623 2624 2625 2626 2627 2628 2629 2630 2631 2632 2633 2634 2635 2636 2637 2638 2639 2640 2641 2642 2643 2644 2645 2646 2647 2648 2649 2650 2651 2652 2653 2654 2655 2656 2657 2658 2659 2660 2661 2662 2663 2664 2665 2666 2667 2668 2669 2670 2671 2672 2673 2674 2675 2676 2677 2678 2679 2680 2681 2682 2683 2684 2685 2686 2687 2688 2689 2690 2691 2692 2693 2694 2695 2696 2697 2698 2699 2700 2701 2702 2703 2704 2705 2706 2707 2708 2709 2710 2711 2712 2713 2714 2715 2716 2717 2718 2719 2720 2721 2722 2723 2724 2725 2726 2727 2728 2729 2730 2731 2732 2733 2734 2735 2736 2737 2738 2739 2740 2741 2742 2743 2744 2745 2746 2747 2748 2749 2750 2751 2752 2753 2754 2755 2756 2757 2758 2759 2760 2761 2762 2763 2764 2765 2766 2767 2768 2769 2770 2771 2772 2773 2774 2775 2776 2777 2778 2779 2780 2781 2782 2783 2784 2785 2786 2787 2788 2789 2790 2791 2792 2793 2794 2795 2796 2797 2798 2799 2800 2801 2802 2803 2804 2805 2806 2807 2808 2809 2810 2811 2812 2813 2814 2815 2816 2817 2

1. Field of the Invention:

The electronic apparatus of the invention include information processing devices, such as note or laptop personal computers and mobile computers, head-mounted displays, video cameras, digital still cameras, car navigation systems, and cellular phones.

In recent years, research and development have been conducted on the liquid crystal panel production technology and resulted in a relatively inexpensive price of the liquid crystal panel. Further, as the information society has progressed in the filed of the Internet and electronic mail, the note type personal computers (hereinafter referred to as note type PCs) have rapidly prevailed.

1

popularity with consumers.

There are two types of liquid crystal panel: a transmission type and a reflection type. The transmission type liquid crystal panel has a backlight installed at the back of the panel whose illumination light passes through the liquid crystal panel to form an image on the display that can be seen by the user. The reflection type liquid crystal panel, on the other hand, does not require a backlight and forms an image by reflecting external light by the liquid crystal panel. The display quality of the reflection type, however, does not match that of the transmission type.

Because the note PCs and digital cameras are used for displaying Internet home pages in color, importance is placed on the display quality such as color reproducibility and the liquid crystal panel for use with these electronic devices needs to be of a transmission type.

Generally, the backlight source for the transmission type liquid crystal panel uses a cold cathode tube that emits white rays. The cold cathode tube is a fluorescent lamp and thus requires a high-voltage AC power supply to be turned on. Hence, the electronic devices such as note PCs require a DC-AC converter for converting a DC power supply into an AC power supply of several hundred volt.

At present, essential factors in improving the portability of

electronic devices are reductions in power consumption, size and weight. Although the power consumption of the liquid crystal panel itself is small, the use of a backlight of a conventional cold cathode tube requires a high voltage, which hinders the reduction in power consumption. Another drawback is that the cold cathode tube has a short life time of about 2,000 hours.

SUMMARY OF THE INVENTION

The present invention has been accomplished in light of the problems described above and provides electronic devices incorporating a liquid crystal panel that has overcome the drawbacks of high power consumption and short longevity (life) of the light source.

In the information device incorporating a liquid crystal panel that overcomes the aforementioned drawbacks, the illuminating light source for the liquid crystal panel comprises:
3-color light emitting diodes for producing three primary colors for additive color mixing; and
a means for mixing rays from the three-color LEDs to produce white light.

In this embodiment, the use of LEDs as a light source for illuminating the liquid crystal panel makes it possible to easily reduce power consumption and size of the electronic device such as

a note PC.

LED is a solid element using the photoelectric conversion effect of a semiconductor. Illuminating an LED requires application of DC voltage of about 1.5 V and thus eliminates the need for the conventional DC-AC converter, which in turn results in a significant reduction in power consumption. The LED is a semiconductor device and thus more reliable and has a smaller size and a longer life than the cold cathode tube.

In the construction described above, the 3-color LEDs for generating three primary colors for additive color mixing -- typically red, green and blue LEDs -- emit color rays of light which are mixed to produce white light that in turn is used for illuminating the liquid crystal panel.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1(A) is an exploded perspective view of an essential part of a transmission type liquid crystal display.

Figure 1(B) is a plan view partially showing a LED light source.

Figure 2 is an external perspective view of a note PC.

Figure 3 is a schematic view showing the construction of the liquid crystal panel.

Figure 4(A) is a schematic view showing the construction of

a main part of a reflection type liquid crystal display.

Figures 4(B) to 4(D) are views for explaining a LED light source.

Figures 5(A) and 5(B) are schematic diagrams showing the arrangement of the liquid crystal panel and the LED light source.

Figures 6(A) and 6(B) are schematic diagrams showing the construction of the LED light source.

Figures 7(A) to 7(F) are external views showing examples of electronic devices.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

The invention will be described by referring to Figures 1 to 7.

Embodiment 1:

This embodiment represents an example in which the present invention is applied to a note PC (personal computer) incorporating a liquid crystal display. Figure 2 shows a rough external perspective view of a note PC 20 which has a liquid crystal display 21 using a color display as a display means.

Figure 1(A) is an exploded perspective view of a main portion of the liquid crystal display 21 which has a scatterplate 11 and an LED light source 12 arranged in that order behind a transmission type liquid crystal panel 10.

As an illumination light source for the transmission type

liquid crystal panel 10 an LED light source 12 is used. The LED light source 12 has LED lamps 13 arranged two dimensionally on a substrate 14. In this embodiment, as shown in Figure 1(B), LED lamps of three colors -- red LED lamps 13R, green LED lamps 13G and blue lamps 13B -- are used. Figure 1(B) is a partial top view of the LED lamps 13, showing the arrangement of the LED lamps 13 on the substrate 14. The three-color LED lamps 13R, 13G, 13B are arranged in delta for uniform distribution over the substrate 14.

The scatterplate 11 is made of a material transparent to a visible light, such as acrylic, polycarbonate and glass. The scatterplate 11 may be formed at its side surface with a reflection plate.

Figure 3 shows an outline construction of the transmission type liquid crystal panel 10. An active matrix substrate comprises a pixel matrix circuit 101, a scan line drive circuit 102 and a signal line drive circuit 103, all formed on a glass substrate 100. The scan line drive circuit 102 and the signal line drive circuit 103 are connected to the pixel matrix circuit 101 through scan lines 121 and signal lines 122. These drive circuits 102, 103 are formed mainly of CMOS circuits.

The scan line 121 is formed for each row of the pixel matrix circuit 101 and the signal line 122 is formed for each column of the pixel matrix circuit 101. Near the intersections of the scan

lines 121 and the signal lines 122, pixel TFTs 110 connected to the scan lines 121 and the signal lines 122 are formed. The pixel TFTs 110 are each connected with a pixel electrode 111 and a capacitor 112.

An active matrix substrate and a counter substrate 200 are bonded together with a liquid crystal sealed between them. The active matrix substrate is formed with external terminals of TFTs during the manufacturing process, and the portions of the active matrix substrate that are formed with the external terminals are not opposed to the counter substrate 200. The external terminals are connected with an FPC (flexible printed circuit) 130, through which external signals and power supply are fed to the circuits 101-103.

The counter substrate 200 is formed with color filters at portions facing the pixel matrix circuits, and the color filters are formed with a transparent conductive film such as ITO film over the entire glass substrate. The transparent conductive film is a counter electrode facing the pixel electrode 111 of the pixel matrix circuit 101. An electric field produced between the pixel electrode 111 and the counter electrode drives the liquid crystal material.

The active matrix substrate has IC chips 131, 132 at the FPC 130 mounting surface. These IC chips are formed with a video

THESE

THESE

THESE

THESE

THESE

THESE

backlight and therefore has the advantages of light weight and low power consumption. However, because external light is used, the display is hard to see in a dark place. This embodiment is intended to improve this drawback.

Figure 4(A) shows the construction of the main part of the liquid crystal panel 10 of this embodiment. At the opposing sides of a reflection type liquid crystal panel 30 are arranged LED light sources 31, which illuminate the reflection type liquid crystal panel 30 so that the display can be seen even in a dark place.

By referring to Figures 4(B) to 4(D), the construction of the LED light sources 31 will be explained. As shown in Figures 4(B) and 4(C), the LED light sources 31 have a first-dimensionally arranged LED lamps 33 and a reflection plate 34 arranged at the back of the LED lamps 33.

As shown in Figure 4(D), the LED lamp 33 comprises a red LED chip 33R, a green LED chip 33G and a blue LED chip 33B arranged on a substrate, with the surface of these chips coated with resin 33a. The surface of the resin 33a is frosted.

The function of the LED light sources 31 will be explained by referring to Figure 4(E). Figure 4(E) shows an outline cross section of the reflection type liquid crystal panel 30. The construction of the reflection type liquid crystal panel 30 is as shown in Figure 3 and a liquid crystal 60 is sealed between glass substrates 40 and

50. The glass substrate 40 on the side of the active matrix substrate is formed with a pixel matrix circuit 41 and a peripheral drive circuit 45.

The pixel matrix circuit 41 is formed with pixel TFTs 42 and pixel electrodes (reflective electrodes) 43 made of metal material. The peripheral drive circuit 45 is formed mainly of CMOS circuits.

On the back of the glass substrate 50 on the counter substrate side are formed triangular wave-shaped inclined surfaces 50a. On the opposite side are formed color filters and counter electrodes.

When an image on the reflection type liquid crystal panel 30 is to be checked in a dark place, the LED lamps 33 of the LED light sources 31 are turned on. The red, blue and green 3-color LED chips 33R, 33G, 33B of the LED lamps 33 are applied with voltages to emit light. Light rays of red, blue and green colors emitted from the LED chips 33R, 33B, 33G are randomly scattered and mixed to form white light LW that goes out from the LED lamps 33.

The white light LW directly emitted from the LED lamps 33 or reflected by the reflection plate 34 enters the glass substrate 50 on the counter substrate side from its side. Because of the inclined surfaces 50a formed at the back of the glass substrate 50, the white light LW repeats being reflected as it propagates through the glass substrate 50 toward the inner part of the panel 30. The

light that has entered is reflected by the reflection electrodes 43, passes through the glass substrate 50, and leaves the liquid crystal panel. The reflected light LR that has penetrated the glass substrate 50 is recognized as a color image by the PC user because it was modified when passing through the liquid crystal.

To ensure that the white light LW can enter the glass substrate 50 efficiently, it may be collected by a lens 70 such as a cylindrical lens before entering the liquid crystal panel 30, as shown in Figure 5(A).

Rather than arranging the LED light sources 31 horizontally with respect to the liquid crystal panel 30, they may be arranged diagonally above the panel to throw the white light LW onto the back (the surface formed with the inclined surfaces 50a) of the glass substrate 50. In this case, too, the lens 70 may be provided as shown in Figure 5(A).

While this embodiment provides two LED light sources 31, only one light source may be used. It is also possible to arrange three or four LED light sources to encircle the liquid crystal panel 30.

Embodiment 4:

Although the reflection type liquid crystal panel of the embodiment 3 is shown to use color filters to display a color

image, it is also possible, as in the embodiment 2, to display a color image by the reflection type liquid crystal panel without using the color filters.

In this case, red, blue and green LEDs are turned on in succession. Instead of using the LED lamps 33 of Figure 4, an LED lamp 90 shown in Figure 6 may preferably be used. The LED lamp 90 in this embodiment has a red LED array 90R, a green LED array 90G and a blue LED array 90B arranged on a substrate 90a and coated with resin 90b.

The LED arrays 90R, 90G, 90B can be turned on independently. At the timing that red, green and blue image data are written into the pixel electrodes, the corresponding color LED arrays can be turned on.

Embodiment 5:

The CMOS circuits and pixel matrix circuits formed according to the invention can be used on a variety of electro-optical devices (active matrix type liquid crystal displays). That is, this invention can be applied to all electronic devices incorporating these direct-viewing type liquid crystal panels.

Such electronic devices include video cameras, digital cameras, head mounted displays (goggle type displays), car navigation equipment, personal computers and mobile information

terminals (mobile computers, cellular phones or electronic books). Such examples are shown in Figures 7(A) to 7(F).

Figure 7(A) shows a personal computer, which comprises a body 2001, an image input section 2002, a display 2003 and a keyboard 2004. This invention can be applied to the image input section 2002, the display 2003 and other signal control circuits.

Figure 7(B) shows a video camera, which comprises a body 2101, a display 2102, a voice input section 2103, operation switches 2104, a battery 2105 and a picture receiving section 2106. This invention can be applied to the display 2102, a voice input section 2103 and other signal control circuits.

Figure 7(C) shows a mobile computer, which comprises a body 2201, a camera section 2202, an image receiving section 2203, an operation switch 2204 and a display 2205. This invention can be applied to the display 2205 and other signal control circuits.

Figure 7(D) shows a goggle type display, which comprises a body 2301, a display 2302 and an arm section 2303. This invention can be applied to the display 2302 and other signal control circuits.

Figure 7(E) shows a player using a recording medium containing programs, which comprises a body 2401, a display 2402, a speaker 2403, a recording medium 2404, and an operation switch 2405. This device can use DVD (digital versatile disc), CD and

others as a recording medium and allows the user to listen music, see movie and perform games and Internet. This invention can be applied to the display 2402 and other signal control circuit.

Figure 7(F) shows a digital camera, which comprises a body 2501, a display 2502, an eyepiece 2503, operation switches 2504 and an image receiving section (not shown). This invention can be applied to the display 2502 and other signal control circuits.

As described above, the range of application of this invention is very wide, including electronic devices in various fields which incorporate the direct-viewing type liquid crystal display. These electronic devices can be implemented by using any combination of the above embodiments 1 to 4.

The use of the LEDs as an illuminating light source for the liquid crystal panel can eliminate the drawbacks of a backlight using a conventional cold cathode tube, such as high power consumption and short life of the light source, and offer reduced power consumption and longer life.